"P

m the interes a dissemination of Earth Resources Survey
Program information and without liability
for any use made thereof."

E7.3 10903. CR-133560

BREAK-UP CHARACTERISTICS OF CHENA RIVER BASIN

(E73-10903) BREAK-UP CHARACTERISTICS OF CHENA RIVER BASIN Semiannual Technical Report, Feb. - Jul. 1973 (Alaska Univ., Fairbanks.) 15 p HC \$3.00 CSCL 08L

N73-29252

Unclas G3/13 00903

Robert F. Carlson Institute of Water Resources University of Alaska Fairbanks, Alaska 99701

July 31, 1973

Second Semi-Annual Technical Report, February-July, 1973 NASA Contract NAS5-21833 ERTS Project 110-5

Prepared for:

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION Goddard Space Flight Center Greenbelt, Maryland 20771

Odicinal photography may be <u>nurchased troma</u>
ENUS Data Center
10th and Dakota Avenue
Sioux Falls, SD 57198

Original photography may be <u>purchased from:</u>
EROS Data Center
10th and Dakota Avenue
Sioux Falls, SD 57198

TECHNICAL REPORT STANDARD TITLE PAGE

		TECHNICA	C KEPUKI SIANU	ARD THEE PAGE			
1. Report No.	2. Government Accession No		3. Recipient's Co	talog No.			
4. Title and Subtitle			5. Report Date				
n 1 01		·	31 July	1973			
Break-up Characteristics of Chena Basin		er	6. Performing Org.				
7. Author(s)			8. Performing Org	onization Report No.			
Robert F. Carlson							
9. Performing Organization Name and			10. Work Unit No.				
Institute of Water Re	esources		·				
University of Alaska Fairbanks, Alaska 99701			11. Contract or Grant No. NAS5-21833				
rarroanko, mraska 9.	,,01		13. Type of Report	and Period Covered			
12. Sponsoring Agency Name and Addr			Type II				
National Aeronautics Goddard Space Flight	ation		- January 197				
Greenbelt, Maryland			14. Sponsoring Age	ncy Code			
Technical Monitor: Mr		-1- (20					
15. Supplementary Notes	• Edward Grump, G	cae_43u					
•	No. 110-5						
1	/UN 596						
Robert F. Carrson	/UN 390		•				
Central Alaska. Cha The VP-8 analyser wa of grey scales and t used to obtain quant snow cover increased beginning of May, wh from 19 Feb. to 27 M melting had started.	as utilized to obtone built in planificative results. I at high altitude tile at lower altifarch, but a decressor flights were used for the state of	to give ain fal meter w It was s from tudes, ase to sed as was foun ude as	the best rese color imate ith computer found, that mid February there was are 2 May, as the "ground truth and that the	esults. ages was the to the a increase ae			
17. Key Words (S. lected by Author(s))	18. Dis	tribution Sta	tement				
ERTS IMAGERY		(-					
SNOW DISTRIBUTION							
HYDROLOGY				.,			
BREAK-UP							
19. Security Classif. (of this report)	20. Security Classif. (of this	page)	21. No. of Pages	22. Price*			
Unclassified	Unclassified						

TABLE OF CONTENTS

SECTION	PAGE
I: INTRODUCTION	1
II: STATUS OF PROJECT A. Objective B. Accomplishments During the Reporting Period 1. Preliminary Investigation 2. Application of ERTS-1 Data to Project Objectives	1 1 1 2
III: NEW TECHNOLOGY	, 3
IV: PLANS FOR NEXT REPORTING PERIOD	3
V: CONCLUSIONS	3
VI: RECOMMENDATIONS	3
VII: PUBLICATIONS	3
VIII: REFERENCES	3
APPENDIX A: CHANGE IN STANDING ORDER FORM	3
APPENDIX B: ERTS DATA REQUEST FORMS	3
TABLE	4
FIGURES 1-6	5-10
APPENDIX C: ERTS IMAGE DESCRIPTOR FORM	11
APPENDIY D. SIGNIFICANT RESHITS	12

I: INTRODUCTION

This report summarizes the work performed and conclusions reached during the second six months of contract no. NASS-21833, ERTS-1 project no. 110-5, "Break-up Characteristics of Chena River Basin".

Receipt, logging, and dissemination of the data for this investigation, and for 11 other University of Alaska ERTS-1 projects is carried out under the auspices of ERTS-1 project 110-1. This project functions as the central coordinating facility for all University of Alaska ERTS-1 projects, and is receiving data to cover the entire state (while the test area of the present project probably does not include more than 1/50 the land area of Alaska).

To date, imagery of about 140 scenes of central Alaska have been received by the present project. However, owing to the high amount of cloudiness, and the relatively short time, we are interested in, only four scenes have been analysed in detail. We found, that for monitoring the break-up band 5 is the most suitable.

II: STATUS OF PROJECT

A. Objective

The original purpose of this investigation was to monitor the break-up in the Chena Basin, Interior Alaska. For this purpose the ERTS-1 imagery has been very successful. In the following sections the details will be described.

B. Accomplishments During the Reporting Period

1. Preliminary Investigation

These have been described in the first semi-annual report.

2. Application of ERTS-1 Data to Project Objectives.

The most interesting period for this project was the spring break up period in Central Alaska. During this time, 2 calibration flights (May 11, 1973 and May 20, 1973) were carried out over the Chena- and Poker-Caribou-watershed, and these were compared with the satellite data.

Most helpful in the analyses of the ERTS data was the zoom transfer scope, which allowed the transfer of contour lines from topographic maps to the ERTS imagery. Furthermore, the VP-8 analyser, purchased under ERTS I 110-1 project, was also used. Not only it is easier to analyse color differences than a grey scale, but the planimeter, which is built into this unit, saves very much time, as planimetering areas with a standard planimeter is very time consuming.

3. Results

In Figure 1 and 2, photographs of the color TV display are given. The area, which is located in Central Alaska, can be seen from Figure 3. When studying Figure 1 and 2, and a topographic map one can see, that the higher areas are snow covered, while areas lower in altitude, show a less dense snow cover. However, one has to be somewhat careful, as vegatation is more dominant in the lower areas, and e.g. a spruce forest, where the same amount of snow was deposited as on a bare area, looks darker. When comparing the two ERTS imageries from March 27 and 2 May 1973, the difference, which can be most clearly seen, is that the area with no or hardly any snow has increased substantially by the latter date. Such color displays are good, to make qualitative statements, but for a quantitative analyses, the planimeter, which is built into the VP-8 unit, was utilized (see table). Starting from 19 Feb. 1973, one can see a strong increase in areas with a total snow cover to 27 March 1973. The percentage of a total snow cover stays relatively constant to 2 May. However, the area, which is bare, increases substantially from end of March to the beginning of May. This is caused by the melting which occurs in the lower lying areas, while the total amount of snow at higher altitudes stays about constant. This is verified by observations of the Soil Conservation Service, which measures the amount of water content in the snow cover at different altitudes (Soil Conservation Service 1973). In Figure 4. the water content is given as a function of altitude for 5 points in the Chena Basin. It can be seen from the graph, that the water content of the snow cover steadily increased from 1 March to 1 May 1973. However, for the lower areas, an increase from 1 March to 1 April was observed. However, in April the melting of the snow cover started, and a smaller value was found on 1 May than 1 April 1973. At the lowest point in the basin, the snow had melted altogether by 1 May 1973. These measurements of the Soil Conservation Service verify the data, we have found from the ERTS imagery, and were given in Figure 1 and 2, and the table, respectively.

The snow cover was also investigated as a function of the slope direction for two relatively small watersheds about 20 miles north of Fairbanks for 11 May 1973. The results can be seen in Figure 5. This investigation was done independently of height. One can see, that areas having an amount of snowcover greater than 50% are found much more frequently on slopes with a northerly exposure than on any other. For Basin A, a result is found that was unexpected viz. slopes with easterly or westerly exposure were slightly more snow free than slopes with southerly exposure. However, this must be regarded as an exception, as the result is not found for the second basin or for the mean of both of them.

In Figure 6, the snow conditions are not only given as a function of slope direction, but also of altitude. One can see, that for slopes with southerly, easterly and westerly directions almost all snow had been melted at lower altitudes. Only northward facing slopes for the two basins had in the mean some snow in the lowest (500-1000 ft) altitude range; 70% had a snow cover of more than 10%, and about 10% of more than 50%. With increasing altitudes and with northerly directions the amount of snow normally increased. It is believed, that this is not the place to discuss further details, as these cannot be understood without further description of the topography as well as information on wind velocities and the related snow drifts.

III: NEW TECHNOLOGY

None.

IV: PLANS FOR NEXT REPORTING PERIOD

In the next 2 months, discharge measurements of the Chena Basin will hopefully become available. The melting of the snow cover will be correlated with these discharge measurements and the meteorological data.

In the remaining time of the grant period the data will be prepared for journal publication.

V: CONCLUSIONS

It has been shown under results, that it is possible to monitor the melting of the snow cover qualitatively with ERTS imagery. The snow conditions were described as a function of time **as** well as a function of altitude and slope direction.

VI: RECOMMENDATIONS

None.

VII: PUBLICATIONS

G. Wendler and R. Carlson: Break-up Characteristics of the Chena River Watershed, Central Alaska. Accepted for presentation at the Interdisciplinary Symposium on Advanced Concepts and Techniques in the Study of Snow and Ice Resources at Asilomar Conference Grounds in Monterey, California, December 2-6, 1973.

VIII: REFERENCES

U.S. Department of Agriculture, Soil Conservation Service, and Alaska Soil Conservation District: Federal-State-Private Cooperative Snow Surveys for Alaska, March, April, May 1973.

APPENDIX A: CHANGE IN STANDING ORDER FORM

None.

APPENDIX B: ERTS DATA REQUEST FORMS

None.

Table


1	2	3	4	5	6		7			
100%	snow cover		decreasing	snow cover		no	sno	W		
11	3	24	23	29	6		4*	19	Feb.	73
29	16	20	16	14	3		2	27	Mar.	73
27	13	16	12	14	. 9		9	2	May	73

Area: 10,000 (nautical miles) 2 or 34,200 km 2 . Values given in percent.

^{*} The brightness level for the data of 19 Feb. 1973 was roughly adjusted for the different shadow length.

ERTS Imagery, 27 March 1973, Channel 5, Photo number 1247-20505-5, False color display with VP-8 unit.

Area can be seen from location map






Figure 1.

ERTS Imagery, 2 May 1973, Channel 5, Photo number 1283-20504-5, False color display with VP-8 unit.

Area can be seen from location map






Figure 2.






Figure 3. The square represents the test area analysed.





>50%

watersheds about 20 miles north of Fairbanks, 11 May 1973.




Figure 6. The snow cover as a function of altitude and slope direction for two watersheds north of Fairbanks, 11 May 1973.

APPENDIX C:

ERTS IMAGE DESCRIPTOR FORM

Univ. of Alaska Inst. of Water Resources

(See Instructions on Back)

DATE July 31, 1973	NDPF USE ONLY
	D
PRINCIPAL INVESTIGATOR Robert F. Carlson	ID
GSFC UN 596	

PRODUCT ID	FREQUENTLY USED DESCRIPTORS*					
(INCLUDE BAND AND PRODUCT)	Rivers	Mtns.	Valleys	DESCRIPTORS		
1211-20504	x	x	. x	Thin layer of cloud		
1231-21021	x	x	x	Mostly cloud covered		
1247-20511	x	×	x			
1262-20340	x	x	x			
1247-20505	x	x	x			
1283=20504	x	x	x			
1284-20562	x	x	x			
1265-20505	x	x	x			
1263-20392	x	x	x			
	·					
()						
].			

^{*}FOR DESCRIPTORS WHICH WILL OCCUR FREQUENTLY, WRITE THE DESCRIPTOR TERMS IN THESE COLUMN HEADING SPACES NOW AND USE A CHECK (\checkmark) MARK IN THE APPROPRIATE PRODUCT ID LINES. (FOR OTHER DESCRIPTORS, WRITE THE TERM UNDER THE DESCRIPTORS COLUMN).

MAIL TO ERTS USER SERVICES
CODE 563
BLDG 23 ROOM E413
NASA GSFC
GREENBELT, MD. 20771
301-982-5406

GSFC 37-2 (7/72)

ORGANIZATION.

APPENDIX D: SIGNIFICANT RESULTS

PRINCIPAL INVESTIGATOR: Robert F. Carlson

TITLE OF INVESTIGATION: Break-up Characteristics of Chena River Basin.

DISCIPLINE: Hydrology

SUBDISCIPLINE: Meteorology

SUMMARY OF SIGNIFICANT RESULTS:

ERTS Imagery has been used to monitor the snow melt in Central Alaska. Channel 5 was found to give the best results. The VP-8 analyser was utilized to obtain false color images of grey scales and the built in planimeter with computer was used to obtain quantitative results. It was found, that the snow cover increased at high altitudes from mid February to the beginning of May, while at lower altitudes, there was an increase from 19 Feb. to 27 March, but a decrease to 2 May, as the melting had started.

Two aerial stereo flights were used as "ground truth" measurement of the ERTS imagery. It was found that the snow cover increased with increasing altitude as well as with a northerly exposure, a result to be expected.